

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000106

International filing date: 14 January 2005 (14.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0400974.2  
Filing date: 16 January 2004 (16.01.2004)

Date of receipt at the International Bureau: 02 March 2005 (02.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT | GB 2005 | 000106  
10 FEBRUARY 2005



INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed 

Dated 20 January 2005



An Executive Agency of the Department of Trade and Industry



70 43 02



19 JAN 04 EB66093-2 D02662  
P01/7700 0.00-0400974.2 ACCOUNT CHA

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

REC/JRP/P64626/000

2. Patent application number

(The Patent Office will fill this part in)

16 JAN 2004

0400974.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

SOLEXA LIMITED  
CHESTERFORD RESEARCH PARK,  
LITTLE CHESTERFORD,  
NR. SAFFRON WALDEN,  
ESSEX. CB10 1XL

07533698002

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UNITED KINGDOM

4. Title of the invention

MULTIPLE INEXACT MATCHING

5. Name of your agent (if you have one)

BOULT WADE TENNANT

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

VERULAM GARDENS  
70 GRAY'S INN ROAD  
LONDON  
WC1X 8BT

Patents ADP number (if you know it)

42001

6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f)

Number of earlier UK application

Date of filing  
(day / month / year)

8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?

YES

Answers YES if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an

applicant, or

c) any named applicant is a corporate body

Otherwise answer NO (See note d)

## Patent Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0  
 Description 27  
 Claim(s) 6  
 Abstract 0  
 Drawing(s) 10

+10 SN

10. If you are also filing any of the following, state how many against each item.

Priority documents 0  
 Translations of priority documents  
 Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0  
 Request for preliminary examination and search (Patents Form 9/77) 1  
 Request for substantive examination (Patents Form 10/77) 0  
 Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Balt Wade Tennant

16 JANUARY 2004

12. Name and daytime telephone number of person to contact in the United Kingdom  
 PALMER; Jonathan Richard  
 020 7430 7500

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.  
 b) Write your answers in capital letters using black ink or you may type them.  
 c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.  
 d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.  
 e) Once you have filled in the form you must remember to sign and date it.  
 f) For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

- 1 -

## MULTIPLE INEXACT MATCHING

## Introduction

The present invention relates to methods and apparatus  
5 for seeking, in a target sequence, an exact or inexact match  
to a given query sequence. In particular, but not  
exclusively, the invention relates to such methods and  
apparatus for use in searching for exact or close matches to  
each of a large number of genetic data query sequences in a  
10 large amount of genetic sequence target data such as a whole  
genome.

## Discussion of the prior art

Computer implemented methods to efficiently search for  
15 one or more query data sequences in a target sequence  
dataset are used in a variety of fields, including searching  
for string query sequences in large numbers of general or  
text computer data files using tools such as UNIX grep and  
agrep, Internet Web searches using search engines such as  
20 Google (RTM) and searches for short sequences of  
polynucleotide or polypeptide data in large genome  
databases.

Wu and Manber, "A Fast Algorithm for Multi-Pattern  
Searching", Tech Report TR-94-17, Department of Computer  
25 Science, University of Arizona, 1994, discloses a computer  
implemented method which simultaneously searches for exact  
matches between multiple query sequences and a target data  
set much more efficiently than can be achieved by carrying  
out corresponding multiple separate searches each for a  
30 single query sequence. Examples apply the method to  
searching large text files for hundreds of different English  
language words simultaneously.

In the method of Wu and Manber, a hash table is built, indexed by the hash value of all possible values of a particular end segment of the query sequences. Each entry in the hash table contains or points to query sequences ending in the corresponding segment. Generally, many entries in the table will be empty, while some entries will point to multiple query sequences. The target sequence is scanned. For each possible matching segment of the target sequence a hash value is generated and used to look up potential query sequence matches using the hash table. Various other techniques, such as the use of a shift table, are used to improve efficiency.


Kim and Kim, "A fast multiple string-pattern matching algorithm", Proc. of 17th AoM/IaOM Conf. on Computer Science, Aug 1999, discloses a broadly similar computer implemented method, but applied to searching for exact matches in a DNA target data set, as well as an English language text target data set. Each nucleotide base type, A, T, G and C, is ascribed a different two bit code, 00, 01, 10 and 11. Query sequences of nucleotide bases (eg TGCAGG) are thereby converted to binary query sequences (eg 011011001010). Each binary query sequence is split into a suffix and a prefix (eg 011011 and 001010). A hash function is applied to each prefix, and the hash value is used as an index into a hash table containing the corresponding suffixes.

A target sequence of nucleotide bases is scanned, base by base. At each position a target fragment of the same size as each query sequence is extracted, binary encoded and divided into prefix and suffix. The hash function is applied to the prefix and the result used as an index into the hash table to obtain the related query sequence suffixes. Each of

which is compared with the target fragment suffix to seek an exact match. The suffix comparison is straightforward and reasonably fast because the test is for an identical match.

Muth and Manber, "Approximate Multiple String Search",  
5 Proc. of 7th Annual Symposium on Combinatorial Pattern  
Matching", pp75-86, 1996, discloses a computer implemented  
method for rapidly searching a large target text database  
for multiple query text strings, allowing for an error of  
one different character in finding an inexact match. Errors  
10 of one different character may be by deletion, insertion or  
substitution of a character. The algorithm uses a hash table  
approach similar to that discussed above. However, each  
query sequence is copied several times and each copy is  
modified by omitting a different character. The target  
15 database is scanned, and each possible matching target  
segment is processed in the same way as each query sequence.  
All the modified target segment copies are compared against  
all the modified query sequences.

The Muth and Manber method for inexact matching is  
20 relatively inefficient even when searching for matches  
subject to just one error, although better than the simplest  
multiple inexact matching method of generating all possible  
error perturbations of each query which should be considered  
a match, and feeding these to an exact matching mechanism.  
25 For a five character query sequence, five modified query  
copies must be compared, using the Muth and Manber method,  
against five modified copies of each possible target  
segment. When two errors are to be considered the number of  
different combinations which must be considered makes the  
30 technique impractical.





It would be desirable to provide an improved computer implemented method and associated apparatus for seeking matches between a large number of query sequences and a large target data set, allowing for a restricted number of differences, or mismatches between a query sequence and a matching target fragment.

It would particularly be desirable to provide such a method and apparatus which reduces the processing time required to make the necessary comparisons.

#### Summary of the Invention

The invention seeks to address the above and other problems of the related prior art. Generally, computer implemented methods of seeking matches between one or more query sequences and one or more target sequences, allowing for limited differences between the query and target sequences, are provided. Also provided are computer apparatus appropriately arranged or programmed to carry out such methods and computer readable media carrying corresponding program code.

The target sequences will usually be overlapping fragments of one or more longer target sequences, each target fragment selected to be the same size as each query sequence.

The invention is particularly useful when applied to the problem of seeking inexact matches between large numbers of query sequences and the target data. In the described embodiments, the invention is used in seeking inexact matches between a large number of short nucleic acid sequences, typically each between about 16 and 32 bases in length, and genome data allowing for up to two sequence differences between each query and a matching genome.

fragment. Such an application is important in analysing the large amounts of nucleic acid data produced very rapidly using contemporary and envisaged genome analysis techniques.

5 The invention is implemented by dividing each query sequence into segments, distributing these segments between first and second segment groups, and using an efficient algorithm to seek potential matches between a first group of segments of each query sequence and a corresponding first group of segments of each target sequence fragment. This  
10 step is repeated using different distributions of segments from each query sequence and target sequence fragment in the compared first groups. The different distributions are arranged such that, whatever the positions of the potential mismatches between a target sequence fragment and a query  
15 sequence being compared, at least one distribution will place all mismatches, up to a certain number, into the second groups. Having found potential matches using a rapid comparison of the first groups, a detailed comparison of the corresponding second groups establishes the required exact  
20 or inexact matches.

The invention may be used with query sequence divided into just two segments, to seek matches subject to just one sequence difference, but is preferably used with four  
25 segments evenly distributed between the first and second groups to find matches subject to up to two sequence differences. In specific embodiments, the first and second groups are referred to as prefix and suffix, but the implied ordering is clearly not essential.

In particular, the invention provides a method of  
30 searching for a plurality of query sequences in a set of target sequence fragments, allowing for mismatches at up to n sequence positions, comprising the steps of

- a) logically dividing each query sequence and each target fragment into at least  $n+1$  segments;
- b) for each query sequence, constructing a first and a second query group by distributing the query sequence segments there between such that at least  $n$  segments are contained in the second query group. Preferably, the method further comprises:
- c) constructing from each target fragment a first target group having the same segment distribution as the first query group; and
- d) for each query sequence, comparing said first query group with each first target group to identify potential matching target fragments. The method may then proceed to find actual matching target fragments, subject to the mismatches to be allowed for, by comparing the second groups or by comparing directly the potentially matching query sequence and target fragment, parts or derivations thereof.

The segments may be formed from simple splitting of the elements of each sequence, or a more complex derivation of segments could be used involving, for example, coding or scrambling. In particular, a segment does not need to be formed from sequence items which are consecutive in the original sequence. For example, a sequence 123456 could be segmented as 123:456 or 135:246 or 621:435 and so on.

Preferably, all segments are the same size as each other, or as nearly the same size as possible given the number of segments and the size of the sequence being split.

Likewise, first and second query and target groups of segments are most conveniently formed using a simple concatenation of segments, in an arbitrary order, but more

complicated schemes involving coding, convolution, scrambling and so on could be used. The relative sizes of

the first and second groups may be optimized having regard to the available computer memory and other resources and features of the data. In the embodiments described, equal sizes of first and second groups is preferable, and allows  
5 for certain additional optimizations.

Each different or distinct distribution of segments into the first and second groups may be described as a hash function. To distribute four segments into two groups there are six such distinct hash functions, bearing in mind that  
10 the order in which the segments are placed in a group is immaterial, as long as the ordering is consistent for the purposes of comparing groups. Preferably, said query sequences and target sequence fragments are logically divided into an even number of segments, and the segments  
15 are distributed in equal numbers between the first and second query and target groups of segments.

To find all potential matches, steps (b) to (d) are repeated using different distributions of segments between said query groups, ideally using all distinct distributions  
20 of segments between said query groups, although it may not be necessary to use all distinct combinations to find at least one match.

For each potential matching target fragment identified in step (d), the following steps are preferably carried out:

25 (e) constructing a second target group having the same segment distribution as the second query group of the potentially matching query sequence; and

(f) comparing said second query group with said second target group to identify a match, allowing for mismatches in  
30 up to n sequence positions.

Step (f) may be efficiently carried out by applying an exclusive OR (XOR) operation between the second query group

and second target group. This is applicable, in particular, if the sequences are encoded as binary numbers, for example using the 2-bit encoding to represent each of the four possible nucleotides in a DNA sequence. By first

5 constructing a lookup table associating each possible outcome of the XOR operation with a match output, which may include a boolean match flag, a number of matches and so on, the output of the XOR operation may be processed more rapidly.

10 The method may be carried out by constructing a first query table indexed by possible values of the first query groups, the entries in the first query table providing access to each second query group by using as an index the value of a corresponding first query group. This first query  
15 table may be described as a hash table, as it represents a mapping between potential first query groups and actual second query groups according to one of the distinct segment distributions, or hash functions.

For each distinct distribution of query sequence  
20 segments, or hash function, there may then be constructed a second query table providing access to each second query group, the entries in the first query table providing references to appropriate entries in the second query table. For each first target group constructed in step (c), step  
25 (d) is preferably implemented by using said first target group to form an index into said first query table. Of course, the tables may be constructed in a variety of ways using any appropriate data structures such as lists, arrays and so on, which may be compressed or compacted as desired.

30 The indexing and referencing may be achieved using pointers, direct numerical indexes, second level hashing and a variety of other techniques familiar to the skilled person.

If two distinct distributions of query sequence segments (or hash functions) are such that the first query group of one distribution is the same as the second query group of the other distribution and vice versa, the query  
5 tables for both of the distinct distributions may be constructed and/or used concurrently, simply by swapping first and second groups of data at appropriate points. This technique may be used to reduce the number of passes required through the target data by a factor of two.

10 The invention also provides computer apparatus, comprising a memory, for searching for a plurality of query sequences in a set of target sequence fragments, allowing for mismatches at up to  $n$  sequence positions comprising: a query groups constructor adapted to construct in the memory,  
15 for each query sequence, first and second query groups by logically dividing each query sequence into  $n+1$  segments and distributing the query sequence segments between the first and second query groups in one or more ways such that at least  $n$  segments are contained in each second query group; a  
20 target groups constructor adapted to construct in the memory, for each target sequence fragment, one or more first target groups having segment distributions corresponding to the first query groups; and a first group comparator adapted, for each query sequence, to compare said one or  
25 more first query groups with corresponding ones of said one or more first target groups and to thereby output a result identifying potentially matching target fragments.

Such apparatus may typically be provided by a personal or desk top computer having a visual display unit, input  
30 devices, a central processing unit, volatile and non

volatile memory and so on. The software for carrying out the method may be provided on removable media such as a CD

ROM, or loaded over a network connection. Query and target data may be loaded and/or stored locally, and/or obtained over a network connection.

## 5 Brief Description of the Drawings

Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1 illustrates steps of a method embodying the  
10 invention;

Figure 2 illustrates in more detail the build hash tables step of figure 1;

Figure 3 illustrates the mask repeats step of figure 2;

Figure 4 illustrates the count prefixes step of figure  
15 2;

Figure 5 illustrates the hash query sequences step of figure 2;

Figure 6 illustrates the scan chromosome step of figure  
1;

Figure 7 illustrates the search for prefix, suffix step  
20 of figure 6;

Figure 8 illustrates the search for suffix, prefix step of figure 6;

Figure 9 illustrates apparatus embodying the invention;  
25 and

Figure 10 illustrates data structures formed in memory by the apparatus of figure 9.

## Detailed description of preferred embodiments

30 A general explanatory embodiment of the invention will first be provided, omitting complex implementation details.

The invention provides a computer implemented method for

- 11 -

seeking matches of a plurality of query sequences of nucleotide bases in a target sequence of nucleotide bases, or indeed a set or database of such sequences, allowing matching with up to 2 substitution errors, whereby a query  
5 sequence and a fragment of a target sequence differ at up to two positions.

Each query sequence is partitioned into four segments A, B, C and D, each containing a roughly equal number of bases. A function is defined  $f_1(ABCD) \rightarrow (P, S)$  that forms a  
10 first group, which will be referred to as a prefix, from two of these four segments and a second group, or suffix, from the remaining two. If a query sequence has been binary encoded, it is straightforward to implement such a function  
15 using bit masking and bit shifting operations. Neglecting the ordering of bases within prefixes and suffixes, there are six such distinct functions:

$f_1(ABCD) \rightarrow (AB, CD)$   
 $f_2(ABCD) \rightarrow (CD, AB)$   
20  $f_3(ABCD) \rightarrow (AC, BD)$   
 $f_4(ABCD) \rightarrow (BD, AC)$   
 $f_5(ABCD) \rightarrow (AD, BC)$   
 $f_6(ABCD) \rightarrow (BC, AD)$

25 Six passes are made through the target sequence. During each pass a different one of the above hash functions  $f_1 \dots f_6$  is used. At each pass a hash table process similar to that described above in respect of the Kim and Kim document is used, except that in the present embodiment the hash  
30 function is used to split query sequences and target

sequence fragments into prefixes and suffixes.



The first step of pass  $i$  is to place the suffix of each query sequence, computed by  $f_1$ , in a hash table using the corresponding prefix as key. The target database is then scanned, base by base. At each base a target fragment is  
5 extracted and  $f_1$  is used to generate the target fragment prefix and suffix. The prefix of the target fragment is used as a key into the hash table, to obtain a set of query sequence suffixes that are to be compared with the suffix of the target fragment.

10 If a target fragment is an exact match to a query sequence, then all six the hash functions  $f_1..6$  will generate identical prefixes for both the target fragment and the query sequence. Consider, instead, an inexact match between a target fragment and a query sequence, with differences at  
15 two base positions. If both differences occur in the same segment, then identical prefixes will be generated for the target fragment and query sequence by three of the six hash functions. The only other possibility is that the differences occur in two different segments, in which case  
20 one of the six hash functions will still generate identical prefixes for the target fragment and query sequence. Thus, whatever the position of the two differences between the target sequence fragment and the query sequence, at least one of the six hash functions yields an identical prefix for  
25 both sequences. For example, if the two differences lie in segments A and C then both differences lie in the suffix of  $f_4$ .

On finding an exact match between the prefixes of the target fragment and the query sequence, the prefix of the  
30 target fragment can be successfully used as a key into the hash table to find the group of suffixes of query sequences having the matched prefix. A search of this group, comparing

the suffix of the target fragment with all the suffixes contained therein subject to up to two differences, will identify the matching query sequence. Of course, not all matching prefixes will have corresponding matching suffixes.

5 Some matching prefixes may be associated with multiple matching suffixes, because several query sequences match the target sequence fragment subject to the up to two differences.

In hash table methods of exact matching, such as that  
10 disclosed by Kim and Kim above, it is sufficient to test for equality between the target fragment and query sequence suffixes. However, for the present purposes a comparison method is desired that is both computationally efficient and capable of detecting the two, or other number of differences  
15 between the suffix, or second group derived from the target fragment and the suffix, or second group, derived from the query sequence. This comparison may be carried out by first computing the bitwise exclusive-OR (XOR) of the binary encodings of the two suffixes.

20 The XOR of two binary numbers contains a 1 at a particular bit position if and only if the two numbers differ at that bit position, so that the number of differences between the suffixes can be counted by counting the positions of the XOR result which contain non-zero bits.  
25 Instead of performing this count for each comparison, a look-up table is preferably pre-calculated which contains the number of non-zero bits for all possible values of the XOR result. In this way, two suffixes can be compared by a single XOR operation followed by the retrieval of a value  
30 from the look-up table. The XOR of the binary encoding of

the two suffixes will contain non-zero bits at any base positions where the two suffixes differ. In particular, XOR

results containing nonzero bits at two, one or zero base positions identify matches between the target fragment and the corresponding query sequence subject to two, one or zero substitution errors respectively.

5

#### Detailed embodiment

A detailed implementation of the invention, and in particular of the embodiment set out above, will now be described with reference to the figures. Again, this  
10 embodiment relates to searching for inexact matches of a large number of query sequences of DNA data in a large target DNA dataset, set out as a plurality of separate chromosome files, and the binary coding scheme discussed above is used. Of course, the method could easily be applied  
15 to other data types, and to search for inexact matches subject to different numbers and types of errors.

The implementation described makes use of the insight that the hash functions  $f_2$ ,  $f_4$  and  $f_6$  described above may be obtained from the functions  $f_1$ ,  $f_3$  and  $f_5$  by simply  
20 exchanging prefixes and suffixes. Advantage is taken of this symmetry by pairing  $f_1$  with  $f_2$ ,  $f_3$  with  $f_4$  and  $f_5$  with  $f_6$ . The hash tables for both members of each pair are generated together, then both hash tables are accessed as the target sequence, set of sequences, or database is scanned. Thus  
25 only three scans through the target data are required.

The problem of searching through both strands of the target sequence or database is handled by generating the reverse complement of each query and hashing that as well. Thus on each scan through the target two hash tables are  
30 constructed for two complementary hash functions, and each table contains an entry for both the forward and reverse complement of each query sequence.

- 15 -

Referring to figure 1, the method is illustrated as a flow diagram. From the start box 102, a new pair of hash functions is selected from  $f_1 \dots f_6$  in the get new hash functions step 104. If all three pairs of hash functions have already been used then control passes to an output results step 106. Otherwise, two hash tables are built by applying the new pair of hash functions to all of the query sequences and their reverse complements in step 108.

Having built the hash tables, the target sequence data is prepared in the step 110 of rewinding the chromosome files, in preparation for the get next chromosome file step 112 which cycles with the scan chromosome step 114 until all chromosome files have been scanned, and matches between the query sequences and target segments have been recorded. When all chromosome files have been scanned control is returned to the get new hash functions step 104 mentioned above.

When all chromosome files have been scanned using all pairs of hash functions the match results are output in output results step 106. This is implemented by a function that interrogates the relevant data structure, which is matchstore discussed below, and outputs the results of the matching process for each query sequence. In the present implementation this output takes the form of one line of ASCII characters for each query sequence, which can be directed to a file. However, the output could equally well be directed to a database.

The get next chromosome file step 112 gets the next of a sequence of chromosome files from a predefined source. In the present implementation a list of file structure directory entries is traversed, but all the chromosome files

could equally well be extracted from a database.

- 16 -

The build hash tables step 108 and scan chromosome step 114 will now be described in more detail.

#### Build Hash Tables Step

- 5        The build hash tables step is implemented using a software function that constructs and populates the data structures outlined below. A C/C++ style notation  $A[i]$  is used to denote the  $i^{\text{th}}$  element of an array  $A$ , with numbering of elements starting at zero.

10

MatchStore: this data structure contains one entry for each query sequence, and is adapted to hold the match results. In the present implementation 8 bytes are used for each entry, and the structure is built as a re-sizeable array, for  
15        example using the "vector" template class in the C++ Standard Template Library. Each entry stores the following information:

- a repeat mask flag to show whether the query sequence was repeat masked (discussed below) or, if not repeat  
20        masked:
- counts of the number of exact, single error and 2 error matches found (each count has a maximum values of 255 in the present implementation); and, if there is a unique best match:
- 25        •        position of the unique best match (comprising chromosome, position on chromosome, forward or reverse strand); and
- positions of the differences between the query and its best match (if there are any).

30

11        This data structure contains two entries for each non-repeat masked query sequence, and implements the second

- 17 -

query tables mentioned above and illustrated in figure 10. Each entry contains the binary encoding of each query sequence suffix (4 bytes in the present implementation). Each entry also contains the entry number of the query  
5 sequence in the MatchStore structure, and a flag denoting whether this is the forward or reverse strand of the query sequence, together requiring another 4 bytes in the present implementation.

10 P1: this data structure contains one entry for each of the possible values of prefix and implements the hash tables, or first query tables mentioned above and illustrated in figure 10. Noting that the prefix is represented as a binary number having a value of between 0 and  $4^{\text{prefixLength}} - 1$  inclusive,  
15  $\text{prefixLength}$  being the number of bases in each prefix, and that there are four different base types, there are  $4^{\text{prefixLength}}$  possible prefixes. Each entry of P1 acts as a pointer into L1, although 32 bit unsigned integers are used in the present implementation. If X is the binary encoding  
20 of a particular prefix, then the entries of L1 corresponding to query sequences that have that prefix are held consecutively in L1, starting with entry P1[X] and stopping at the entry immediately before P1[X+1].

L2 and P2 are structures which are essentially the same  
25 as L1 and P1, except that the roles of the prefix and suffix are reversed, thereby implementing the reverse hash function.

To populate the data structures, the query sequences are read in a predefined order from one or more source  
30 files, with some mechanism provided to identify when all the query sequences have been read so that the source files can be rewound. In the present implementation query sequences

- 18 -

are read from an ASCII file, but they could equally well be extracted from a database or other storage mechanism.

The build hash tables step 108 is broken down into a number of sub-steps as shown in figure 2. A mask repeats  
5 step 120 is followed by a count prefixes step 122, then a hash query sequences step 124.

The mask repeats step 120 is illustrated in more detail in figure 3. The aim of this step is to prevent the matching  
10 process from being dramatically slowed down or from becoming inefficient by the matching of any one query sequence to a large number of different target sequence segments.

In the mask repeats step 120 a repeat list containing DNA repeat sequences already known to recur, or expected to recur many times in the target data is read. This is  
15 illustrated in figure 3 as the cycle between the get next repeat sequence step 130 and the add to repeat list step 132.

When there are no more repeat sequences to be read, processing moves on to reading the query sequences, in the  
20 get next query sequence step 134. For every query sequence read, a size variable, initially set to zero, is incremented in step 136. If the new query is not found in the repeat list by the subsequent find query in repeat list step 138 then control is returned to the get next query sequence step  
25 134, for the next query sequence to be read. If the new query is found in the repeat list by step 138 then the MatchStore structure is resized in step 140 to the size indicated by the size variable, and the repeat mask flag of the MatchStore entry indexed by the size variable is set in  
30 step 142. Control is then returned to the get next query sequence step 134.

- 19 -

When there are no more query sequences to be read, MatchStore is resized in step 144 to the size indicated by the size variable, and the repeat list is deleted in step 146.

5       The count prefixes step 122 of figure 2 is illustrated in more detail in figure 4. The aim of the count prefixes step is to count the number of occurrences in the query sequences of each possible prefix into P1, and of each possible suffix into P2. The structures P1 and P2, as  
10       described above, are first created, in step 150. The query sequence file of files are then rewound, in step 152.

      The query sequences are then read and processed sequentially by a repeating series of steps beginning with a get next query sequence step 154, until no more queries are  
15       available to process. Each query sequence read in step 154 is tested in step 156 to determine if it is found in the repeat list discussed above, by checking the appropriate repeat mask flag of MatchStore. If it is found in the repeat  
20       list then control is passed back to step 154 to get the next query sequence. Otherwise, the prefix and suffix of the query sequence are derived in step 158, and counted into P1 and P2 respectively in step 160 by incrementing the element  
25       of P1 or P2 indexed by the prefix or suffix. The query sequence is then replaced by its reverse complement in step 162, the prefix and suffix of the reverse complement are derived in step 164 and the newly derived prefix and suffix are counted into P1 and P2 in step 166. Control is then  
      returned to the get next query sequence step 154.

      The hash query sequences step 124 of figure 2 is  
30       illustrated in more detail in figure 5. The aim of this step is to populate the L1 and L2 structures. The first sub-step is the finish P1, P2 step 180 in which P1 and P2 are



traversed, and converted into cumulative sums. The last elements of P1 and P2 then indicate the total number of non repeat masked query sequences, including both forward and reverse complements, and hence the required sizes for L1 and L2. These sizes are used in the subsequent step 182 of creating the L1 and L2 structures, following which the one or more query sequence files are rewound in step 184, ready to be read again.

The query sequences are then read and processed sequentially by a repeating series of steps beginning with a get next query sequence step 186, until no more queries are available to process. Each query sequence read in step 186 is tested in step 188 to determine if it is found in the repeat list discussed above, by checking the appropriate repeat mask flag of MatchStore. If it is found in the repeat list then control is passed back to step 186 to get the next query sequence. Otherwise, the prefix and suffix of the query sequence are derived in step 190, and written into the L2 and L1 structures respectively in step 192. The query sequence is then replaced by its reverse complement in step 194, the prefix and suffix of the reverse complement are derived in step 196 and the newly derived prefix and suffix are written into L2 and L1 in step 198. Control is then returned to the get next query sequence step 186.

25

#### Scan chromosome step

In this step a chromosome sequence is scanned, base by base. At each base position, where possible, a target sequence fragment of the same length as the query sequences is extracted. This may not always be possible: if the target fragment contains a code indicating an unknown or ambiguous

- 21 -

base then the fragment is ignored, and the process skips to the next useable fragment.

Each chromosome file could be an ASCII file, but in the present implementation one or more binary files using the 2-  
5 bits-per-base binary encoding discussed above provide the target data. Ambiguity codes are handled by maintaining a separate list of "valid" regions free from ambiguity codes, each region being defined by a start and a stop position.

The scan chromosome-step is illustrated in more detail.  
10 in figure 6. The get next chromosome fragment step 210 obtains the next target fragment available from within the valid regions mentioned above. The prefix and suffix of the target fragment are then obtained using the current hash functions in step 212. The target fragment prefix and suffix  
15 are sought in P1 and L1 respectively in step 214, and the suffix and prefix are sought in P2 and L2 respectively in step 216. Control is then passed back to the get next chromosome fragment step 210.

When no more chromosome fragments are available the  
20 scan chromosome task 114 of figure 1 is complete.

The step 214 of seeking the current target fragment prefix and suffix in P1 and L1 is further illustrated in figure 7. In step 220 a count variable i is set to the value of P1 corresponding to the present target fragment prefix.  
25 Variable i is then used to count through the entries of L1 corresponding to all the queries having the same prefix; by means of increment step 226 until i is equal to the value of P1 corresponding to the next possible prefix, as determined by test step 222, at which point the step 214 of figure 6 is  
30 complete.

For each value of count variable i, the query sequence suffix held in L1[i] is compared, in step 224, to the

present target fragment suffix. In this way, the target suffix is compared with the suffixes of all query sequences that have the same prefix as the target fragment. As discussed above, this is achieved by taking the bitwise  
5 exclusive-OR of the binary encoding of the target suffix with the binary encoding of each query suffix, and then using the result to index into a lookup table to find the number of mismatches and their positions.

Comparisons revealing more than two mismatches are of  
10 no interest in the present implementation. However, it will be recalled that matches having mismatch errors in two distinct segments will be found using only one of the six hash functions, those having mismatch errors in only one segment will be found using two of the hash functions, and  
15 exact matches will be found using all six hash functions. For this reason, the results of comparisons revealing mismatches in two distinct segments are always stored, but by choosing to ignore other types of matches on certain passes it is ensured that an exact or inexact match is  
20 registered only once.

The decision whether or not to store a match found using comparison step 224 is made in store decision step 229. If a positive decision is made, the comparison results are stored in the MatchStore structure in step 230. In  
25 either case, control is returned to test step 222 by way of increment step 226.

The step 216 of seeking the current target fragment suffix and prefix in P2 and L2 respectively is further illustrated in figure 8. It will be seen that the steps of  
30 figure 8 are identical to those of figure 7, except that P1 is replaced by P2, L1 by L2, "prefix" by "suffix", and "suffix" by "prefix", such that the roles of the suffix and

prefix are reversed and the complementary hash function implemented.

### Apparatus

5           Computer apparatus for putting the above described methods into effect is illustrated in figure 9. Query sequences 302 and target sequences 304 are stored in volatile or non volatile memory, for example in a database or on a hard disk drive. A query groups constructor element  
10   310 is provided by software running on the computer, and constructs query groups from segments of the query sequences, as determined by data or program elements 312 representing the hash functions, or segmentation distributions to be used.

15           A fragmentor element 314 takes target sequence data 304 and from it forms target sequence fragments of the same length as the query sequences. The fragmentor avoids target sequences containing ambiguity codes by referring to a list of valid regions.

20           Target sequence fragments are passed to the target groups constructor 316, which constructs target groups of segments of the target fragments, also under the control of the data or program elements 312 defining the hash functions or segment distributions to be used.

25           The query groups constructor 310 forms pairs of first and second query groups 318, 320 of segments for each query sequence and each hash function. The target groups constructor 316 forms corresponding pairs of first and second target groups 322, 324 of target fragment segments,  
30   for each target sequence fragment and each hash function.

Each first target group 322 is compared with each first query group 318 by means of a first comparator mechanism

326, which is implemented using the hash table methodology discussed above, and illustrated as the first query table 340 in figure 10. An exact match between a first query group 318 and a first target group 322 indicates a possible match between the corresponding full query sequence and target fragment. This possible match is signalled to a second group comparator mechanism 328 which compares the associated second query and target groups, making use of the second query table 342 illustrated in figure 10. If the second groups match, subject to the maximum number of mismatches allowed according to the hash functions 312 used, then a match result is output by output element 330. The second group comparison is preferably implemented, as discussed above, by an XOR operation, the result of which is used as an index into a lookup table 332.

Some data structures formed in memory by the apparatus of figure 9 and the method described in connection with figures 1 to 8 are shown in figure 10. Query sequences 302 and hash function or segmentation definitions 312 are jointly used to create a set of first query tables 340. There is a query table for each hash function, each table being indexed by the possible values of first query groups of query sequence segments which could be produced using the corresponding hash function. The elements of each first query table, or hash table, provide references into entries of a corresponding second query table 342. There is a second query table for each hash function. Each second query table contains the suffixes, or second query groups of segments actually produced using the corresponding hash function.

Using the data structures illustrated in figure 10, a target fragment is processed using a hash function to form a

prefix, or first query group, and the corresponding entry in the first query table 340 for the same hash function is used to find the entries in the appropriate second query table 342 containing query sequence suffixes which might confirm  
5 an exact or in exact match.

Of course, the query tables for the different hash functions do not need to coexist in memory at the same time, although simultaneous construction and/or use of tables corresponding to a complementary pair of hash functions may  
10 be advantageous, as already discussed.

#### Specific implementation

The described method and apparatus were used, in particular, to search for exact or inexact matches between  
15 large numbers of short DNA query sequences and target sequences in a database containing relatively small numbers of large DNA sequences structured in files by chromosome. In one implementation, a batch of about 12 million query sequences of between 16 and 32 bases in length were scanned  
20 against a target database of build 33 of the human genome. This version of the human genome comprised files for each of the 22 autosomal chromosomes and each of the 2 sex chromosomes, containing about 3 billion bases in total. This was carried out on an Intel Pentium desktop computer with a  
25 microprocessor clock speed of 2GHz and 1GByte of RAM, running the well known RedHat Linux 7.2 operating system. The method was implemented using software code written in C++ and compiled using the well known GNU C/C++ compiler.

#### 30 Variations and extensions

The methods discussed in detail above are a special case of a more general method that seeks matches subject to

$m$  differences by splitting query sequences into  $n$  fragments, where  $n > m$ . Generally,  ${}^nC_m = n!/(m!(n-m)!)$  passes through the target databases will be used, each time carrying out the hash table scheme using a different one of the  ${}^nC_m$  ways of choosing  $n$  minus  $m$  fragments for exact matching the prefixes and  $m$  fragments for inexact matching of the suffixes. In the above detailed examples, setting  $n = 2m$  allows hash functions to be paired, leading to greater computational efficiency.

- 10 By way of example, if  $n = 2$  and  $m = 1$ , then the method will find inexact matches subject to a single mismatch using two hash functions, which are trivial in that they merely define a prefix and suffix, and a corresponding suffix and prefix. If  $n = 3$  and  $m = 2$ , then the method will find
- 15 inexact matches subject to two mismatches using three hash functions, but may be much less efficient than using  $n = 4$  and  $m = 2$  because the sizes of the hash tables stored in the  $P$  data structures will be rather small, and the number of query suffixes for any given query prefix rather large.
- 20 If  $n = 6$  and  $m = 3$ , all three-error matches can be found in 20 passes through the target data, or in 10 passes if complementary hash functions are paired together as already described.

For a given number of allowable errors to accommodate

25 an inexact match, i.e.  $m$ , a higher value of  $n$  would be expected to make each pass faster, but there will be more passes to complete. For greater  $n$ , the lookup tables  $P1$  and  $P2$  also rapidly become very large, and may not fit into fast memory. To fine tune the method to cope with this,  $P1$  and  $P2$

30 may contain only most significant bits of the prefixes, with

the least significant bits being accommodated in  $L1$  and  $L2$ . However, lookup of suffix information then requires an

- 27 -

additional binary search phase following the initial table lookup. This scheme has been tried for query sequence lengths greater than 26 bases, and it works well without being detrimental to the speed of the method.

5        The number of allowable errors in an inexact match  $m$  is likely to be governed by the application to which the method is being put, while the value of  $n$  to optimize the method will be very hardware dependent, in particular being governed by the amount of fast memory available to  
10 accommodate the required data structures.



CLAIMS:

1. A method of searching for a plurality of query sequences in a set of target sequence fragments, allowing  
5 for mismatches at up to  $n$  sequence positions, comprising the steps of:
  - a) logically dividing each query sequence and each target fragment into at least  $n+1$  segments;
  - b) for each query sequence, constructing a first and a  
10 second query group by distributing the query sequence segments there between such that at least  $n$  segments are contained in the second query group;
  - c) constructing from each target fragment a first target group having the same segment distribution as the  
15 first query group; and
  - d) for each query sequence, comparing said first query group with each first target group to identify potential matching target fragments.
- 20 2. The method of claim 1 wherein steps (b) to (d) are repeated using different distributions of segments between said query groups.
3. The method of claim 2 wherein steps (b) to (d) are  
25 repeated using all distinct distributions of segments between said query groups.
4. The method of any preceding claim further comprising, for each potential matching target fragment identified in  
30 step (d), the following steps:

- 29 -

(e) constructing a second target group having the same segment distribution as the second query group of the potentially matching query sequence; and

(f) comparing said second query group with said second target group to identify a match, allowing for mismatches in up to n sequence positions.


5 5. The method of claim 4 wherein step (f) is carried out by applying an exclusive OR operation to binary representations of the second query group and second target group.

6. The method of claim 5 wherein the result of said exclusive OR operation is analysed using a lookup table.

15 7. The method of any preceding claim further comprising, for each distinct distribution of query sequence segments, constructing a first query table indexed by possible values of the first query groups, the entries in the first query table providing access to each second query group by using as an index the value of a corresponding first query group.

25 8. The method of claim 7 further comprising, for each distinct distribution of query sequence segments, constructing a second query table providing access to each second query group, the entries in the first query table providing references to appropriate entries in the second query table.

30 9. The method of claim 7 or 8 further comprising the step of, for each first target group constructed in step (c),



- 30 -

implementing step (d) by using said first target group to form an index into said first query table.

10. The method of claim 7, 8 or 9 wherein, if two distinct  
5 distributions of query sequence segments are such that the first query group of one distribution is the same as the second query group of the other distribution, said query tables for both of the distinct distributions are constructed and/or used concurrently.

10

11. The method of any preceding claim wherein said target sequence fragments comprise overlapping fragments of one or more target sequences.

15 12. The method of any preceding claim wherein said query sequences and target sequence fragments comprise biochemical sequence data.

13. The method of claim 12 wherein said query sequences and  
20 target sequence fragments are binary encoded.

14. The method of any preceding claim wherein  $n$  is at least two.

25 15. The method of any preceding claim wherein said query sequences and target sequence fragments are logically divided into an even number of segments, and the segments are distributed in equal numbers between the first and second query and target groups.

30

16. Computer apparatus comprising elements adapted to carry out the method of any preceding claim

17. A computer program product carrying computer program code comprising elements adapted to carry out the method of any of claims 1 to 15 when executed on a computer.

5

18. A computer readable medium comprising computer program code adapted to carry out the method steps of any of claims 1 to 15 when executed on a computer.

10 19. Computer apparatus comprising a memory, for searching for a plurality of query sequences in a set of target sequence fragments, allowing for mismatches at up to  $n$  sequence positions comprising:

15 a query groups constructor adapted to construct in the memory, for each query sequence, first and second query groups by logically dividing each query sequence into  $n+1$  segments and distributing the query sequence segments between the first and second query groups in one or more ways such that at least  $n$  segments are contained in each  
20 second query group;

a target groups constructor adapted to construct in the memory, for each target sequence fragment, one or more first target groups having segment distributions corresponding to the first query groups; and

25 a first group comparator adapted, for each query sequence, to compare said one or more first query groups with corresponding ones of said one or more first target groups and to thereby output a result identifying potentially matching query sequences and target fragments.

30

20. The apparatus of claim 19 wherein the query groups constructor and target groups constructor are adapted to

construct, for each query sequence and target fragment respectively, a plurality of groups having all distinct distributions of segments between said first and second groups.

5

21. The apparatus of claim 19 or 20 wherein the target groups constructor is adapted to construct, at least for each target sequence fragment identified by the first group comparator as a potentially matching target fragment, one or  
10 more second target groups having segment distributions corresponding to the second query groups, and further comprising a second group comparator adapted, for each identified potentially matching query group and target fragment, to compare the corresponding second query group  
15 and second target group to identify a match allowing for mismatches in up to  $n$  sequence positions.

22. The apparatus of any of claims 19 to 21, further adapted, for each distinct distribution of query sequence  
20 segments, to construct in the memory a first query table indexed by possible values of the first query groups, the entries in the first query table providing access to each second query group by using as an index the value of a corresponding first query group.

25


23. The apparatus of claim 22 further adapted, for each distinct distribution of query sequence segments, to construct in the memory a second query table providing access to each second query group, the entries in the first  
30 query table providing references to appropriate entries in

the second query table.

24. A method of searching for a plurality of query sequences in a set of target sequence fragments substantially as herein described with reference to the accompanying drawings.

30 45 02

1/10

Fig. 1



10 45 00

2/10




Fig. 2

10 45 02

3/10




Fig. 3

70 45 02

4/10




Fig. 4

10 45 02

5/10




Fig. 5



10 45 02

6/10




Fig. 6

16 45 02

7/10




Fig. 7

10 45 00

8/10





Fig. 8

16 45 02

9/10





10 \* 5 02




Fig. 10

70 45 02

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**